INSTANT REMOVER

INSTANT CLEANER FOR FRESH CEMENT GROUT

PORCELAIN TILES, CERAMIC TILES, GLASS MOSAIC, QUARRY TILES



WHAT IT'S FOR

- Removes fresh cement grout residue, including grouts containing additives
- Ideal for cleaning the backs of large format tile before laying
- Perfect for cleaning grout floats and application tools
- Prevents the dull smears or streaks caused by failure to remove grout residue

ADVANTAGES

- **RAPID DRY TECHNOLOGY**: fast-acting, to be used during the laying process
- Does not foam
- Does not damage materials or grout
- High coverage
- Does not damage aluminium or steel trims
- For indoor and outdoor use, on walls and floors
- **PATENTED**: application system with effective and certified results



COVERAGE

COVERAGE (750 ml):	
Large format tile	up to 350 linear metres
Mosaic	up to 15 m^2

Coverage shown is indicative

Packaging

750 mL spray bottles in boxes of 12.

WARNINGS
- Keep out of reach of children.
- Do not disperse into the environment after use.

TEMPERATURES
Storage temperature: from 5° to 30° C.
The product should be applied to materials with temperature between 5° and 30°C.

HOW TO USE IT

No dilution required:
ready to use.
Application:
To remove cement grout residue during installation: wait for the grout to initially set and become firm to the touch (usually about 10 to 30 minutes, according to the grout manufacturer's instructions). Carry out an initial cleaning of the surface with a sponge dampened with clean water.
Then, complete the cleaning process following the steps below.
Spray I**NSTANT REMOVER** evenly on the damp surface.
Let sit for 1-2 minutes, depending on the material finish.
Clean using a sponge float, rinsing it often to keep it clean.
For stubborn stains, repeat the above instructions after one hour.
Refer to the grout manufacturer's instructions for indications about when the surface is safe to use.
Cleaning with **INSTANT REMOVER** can only take place during the installation process.
To clean cement grout residue that has cured on the surface, use **DETERDEK PRO** acid cleaner for post construction cleaning.

Caution:
Do not use on polished marble and acid sensitive materials.
Test the product on a small, inconspicuous area of the surface to check the grout's resistance to the product.
If the flooring contains aluminium elements, the product can be applied according to the above instructions.
Do not use abrasive sponges.
Do not press too hard during cleaning to avoid damaging the grout.