ULTRACARE MULTICLEANER

Concentrated cleaner with a very high yield for everyday cleaning and maintenance of surfaces



BENEFITS AND FEATURES

- Indoor, outdoor, walls and floors
- High yield
- Floor cleaner
- Biodegradable
- Highly concentrated (to be diluted)

CO_2e FULLY OFFSET PRODUCTS

Residual Greenhouse Gas emissions measured throughout the life cycle of this product using Life Cycle Assessment (LCA) methodology, verified and certified with EPDs, have been offset for the year 2026 through the acquisition of carbon credits in support of forestry protection projects. For more details on emission calculations and offsetting projects, visit mapei.com.

WHERE TO USE

Cleans effectively and non-aggressively, respecting the material and any protector applied. Suitable for use on:

- porcelain and ceramic tiles;
- concrete flooring;
- parquet with oil or paint finish;
- terrazzo and terracotta;
- marble, granite and all natural stone, perfect for use on polished natural stone that is sensitive to aggressive detergents;
- quartz and marble agglomerates;
- flooring in LVT, linoleum, rubber and PVC.
- acrylic resin flooring created using **Mapecoat TNS** range.

PRODUCT INFORMATION

UltraCare Multicleaner is a concentrated cleaner. Its special formula guarantees a high level of cleanliness respecting the surfaces on which it is used. It is suitable for use on all washable surfaces, even the most delicate thanks to the neutral pH. It is also characterized by a pleasant scent.

UltraCare Multicleaner when diluted (1 : 200) does not require rinsing as it leaves no residues and/or halos on the surfaces and can be used both indoors and outdoors.

It is effective for ordinary and extraordinary maintenance operations depending on the degree of dilution as detailed below.

Used regularly it keeps colours vivid and retains the appearance of the surfaces on which it is used.

RECOMMENDATIONS

- Never use **UltraCare Multicleaner** on waxed surfaces at high concentration. In case of doubt, carry out a preliminary test in an inconspicuous area to define the proper dilution needed.
- Do not use **UltraCare Multicleaner** undiluted.
- When using **UltraCare Multicleaner** we advise to wear rubber gloves.
- Use on methacrylate baths only when diluted.
- **UltraCare Multicleaner** does not damage metal or galvanized surfaces; however, given the variety of materials available on the market, a preliminary test at different concentrations is always recommended.

APPLICATION PROCEDURE

Dilute **UltraCare Multicleaner** with water in ratio from 1 : 20 to 1 : 200 depending on the degree of concentration required and the level of dirt to be removed.

UltraCare Multicleaner can be used diluted 1 : 30 to undertake the initial clean after installation on delicate surfaces.

For routine maintenance dilute **UltraCare Multicleaner** 1 : 200 (50 ml of product in 10 litres of water). In this dilution it is not necessary to rinse the treated surfaces.

For extraordinary maintenance or more resistant dirt use the product at higher concentrations up to 1 : 20 (500 ml of product in 10 litres of water). At these dilutions it is necessary to rinse the surfaces with water.

You can use the product altering the dilutions to those described above making it adaptable to your specific needs. The surface must be rinsed when used in a dilution other than 1 : 200. Please ensure that the surface is rinsed with plenty of clean water.

You can use **UltraCare Multicleaner** in floor cleaning machines following the instructions of the machine manufacturers.

CONSUMPTION

Diluted in a ratio of 1 : 200 with water it is possible to clean approximately 1500 m^2 of surface area with a litre of **UltraCare Multicleaner**. Consumption may vary based on dilution, the degree and type of dirt and the surface to be treated.

PACKAGING

UltraCare Multicleaner is available in 1 and 5 litres tanks.

STORAGE

UltraCare Multicleaner, stored in the original packaging, has a storage time of 3 years.

SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

Instructions for the safe use of our products can be found on the latest version of the Safety Data Sheet, available from our website www.mapei.com.

PRODUCT FOR PROFESSIONAL USE.

TECHNICAL DATA (typical values)

PRODUCT IDENTITY	
Consistency:	liquid
Colour:	transparent
Density:	1.00 g/cm³
pH:	8
Recommended temperature range:	0°C to +40°C
Waiting time before rinsing:	5 minutes

WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.

Please refer to the current version of the Technical Data Sheet, available from our website www.mapei.com

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in force at the time of the MAPEI product installation.

The most up-to-date TDS can be downloaded from our website www.mapei.com.

ANY ALTERATION TO THE WORDING OR REQUIREMENTS CONTAINED OR DERIVED FROM THIS TDS EXCLUDES THE RESPONSIBILITY OF MAPEI.

Mapei S.p.A.

Via Cafiero, 22, 20158, Milano

+39-02-376731 www.mapei.com mapei@mapei.it

11005-7-2026 en (IT)

Any reproduction of texts, photos and illustrations published here is prohibited and subject to prosecution