# NOPAINT STAR

## GEL CLEANER FOR WALLS

**PORCELAIN TILES, MARBLE, GRANITE, NATURAL STONE, AGGLOMERATES, GLAZED CERAMIC TILES, CONCRETE, PLASTER, TERRACOTTA, QUARRY TILES**




**NOPAINT STAR** is a fast-action, effective paint stripper for walls that removes graffiti from treated and untreated walls. Provides in-depth cleaning and degreasing. Cleans smog and dust from external walls. Removes film-forming and coating products from terracotta surfaces.



## WHAT IT'S FOR

- Removes graffiti from treated and untreated walls: it is particularly effective on rough or porous surfaces (concrete/plaster walls, exposed brick, natural stone...).
- Removes the **WET STONE ECO** and **WET ECO** protective agents if they have been incorrectly applied or when thorough cleaning is required
- Viscous consistency: ideal for wall applications.
- Provides in-depth cleaning and degreasing.
- Cleans smog and dust from exterior walls.
- Removes film-forming and coating products from terracotta surfaces.

## ADVANTAGES

- Easy to use.
- Ready to use: no dilution required.
- Water-based paint remover.
- Rapid and highly efficient

## HOW TO USE IT

**No dilution required:**
ready to use.
**Application:**
1. Apply the product directly on the wall with a large, flat paintbrush or using the airless method.
2. Leave for at least 5 minutes.
3. Intervene with mechanical means.
4. Rinse.

For best results, use a water-jet cleaner on vertical surfaces and a single-disc cleaning machine on floors.
Repeat application of the product and the consequent rinsing, if necessary (for example, on porous surfaces such as exposed brick, natural stone etc.).
To remove possible residues of film-forming protective products such as **WET STONE ECO** and **WET ECO** in the event of incorrect application: apply the undiluted product directly onto the surface using a brush or by spraying.
Leave to react for 15 minutes, rub with a brush or single-disc machine and rinse well with water.
Repeat the application in the event of obstinate treatments.

**CLEANING OF TOOLS:** clean with water after use.

## COVERAGE

| COVERAGE (1 litre): |
|---|
| 5 $m^2$ |

Coverage rates are indicative.

### Packaging

1 litre: boxes of 12.

**WARNINGS**
- Keep out of reach of children.
- Do not disperse into the environment after use.

**TEMPERATURES**
Storage temperature: from 5° to 30° C.
The product should be applied to materials with temperature between 5° and 30°C.

***Caution:***
*If the applied product tends to dry on the surface, add a small amount of water to activate it. Check the detergent's compatibility with the type of surface before application. On coloured plaster, carry out a spot test beforehand to check whether any colour changes.*