HYDROREP ECO

WATER-BASED TECHNOLOGY

WATER REPELLENT PROTECTION

UNPOLISHED STONE AND AGGLOMERATES, CONCRETE, TERRACOTTA, EXPOSED BRICKS, QUARRY TILES, PLASTER, TUFF



Anti-fouling tested in accordance with the **UNI EN ISO 846:1999 standard.** The formulation limits the deterioration of the surface when exposed to organic decay.



COVERAGE

COVERAGE (1 litre):	
Terracotta, exposed brick walls, quarry tiles, stone, plaster	10-20 m²
Concrete	8-10 m²

Coverage shown is indicative and refers to single coats

Packaging

1 litre: boxes of 12.
5 litres: boxes of 4.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- Outdoor flooring must be properly laid before being treated and must satisfy all the specific requirements, including: adequate sloping, properly executed expansion joints, perfect isolation from the underlying ground, proven compatibility with sub-zero temperatures. It does not protect marble and limestone from acid.

TEMPERATURES

Storage temperature: from 5° to 30° C.
This product must be applied to surfaces with temperature between 10°C and 30°C.

WHAT IT'S FOR

- Water-repellent with natural finish.
- Deeply penetrates the material while allowing the surface to breathe.
- Hampers the build-up of algae, moulds and lichen.
- Protects the surface against deterioration caused by weathering.

ADVANTAGES

- Anti-fouling barrier certified by tests conducted in conformity to the UNI EN ISO 846: 1999 method
- Ideal for protecting exterior walls
- Resists UV radiation
- Does not alter terracotta frost resistance
- It protects against efflorescence
- Can be applied to surfaces with residual moisture: drastically reduced application times
- The treatment preserves the material's level of breathability above 90%
- An **A+** classified product in accordance with the French VOC regulation

HOW TO USE IT

No dilution required:
ready to use.

Application: Make sure that the surface is dry and clean, then apply the product by impregnating the material until it is saturated, using a brush or other application method. Dab any excess product with a clean cloth before it dries (roughly 10-15 minutes). The surface can be walked on after 4 hours. The water-repellent effect starts after 24 hours.

CLEANING OF TOOLS: clean with water after use.

FOR PROFESSIONAL USE ONLY: to apply the product with an airless system or other spray applicators, use the appropriate PPE, as indicated in the safety data sheet.

Caution:
Since there are so many different materials, before applying the product we recommend testing it on a small area of the surface to check for any colour changes. Avoid surface pooling.
*Do not apply the product outdoors if rain is forecast. Any stubborn product residues can also be removed when dry, by using **FASEZERO** diluted 1:10 and a white disc.*
Avoid applying on surfaces with condensation and under direct sunlight.
Does not protect against acid aggression.