WET STONE ECO

CONSOLIDATING PROTECTOR WITH A GLOSS FINISH

ROUGH TEXTURED NATURAL STONE AND AGGLOMERATES (SPLIT FACE, TUMBLED, FLAMED, ETC.), TUFF

WATER-BASED TECHNOLOGY



WHAT IT'S FOR

- Gives an enhanced, wet look to rough textured natural stone surfaces (split face, tumbled, flamed)
- Protects the material against stains and dirt
- Prevents surface dusting

ADVANTAGES

- Water-based treatment
- Particularly suited for exterior use; also effective in interiors
- Stainproof and dirt repellent action
- Surface consolidating agent
- High resistance to heavy traffic
- Resistant to weathering
- UV resistant and non-yellowing
- Eases subsequent maintenance
- Provides a glossy enhanced look that can be intensified with additional coats
- An A+ classified product in accordance with the French VOC regulation



COVERAGE

COVERAGE (1 litre):
10-20 m²

Coverage shown is indicative and refers to single coats

Packaging

1 litre: boxes of 12.
5 litres: boxes of 4.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- In order to be treated, outdoor paving must be installed correctly and according to current installation regulations (UNI 11714-1 standard).

TEMPERATURES

Storage temperature: from 0° to 30°C.
Must be applied at temperatures between 10°C and 30°C.

HOW TO USE IT

Ready for use:
Shake before use.
On a clean, dry surface, apply **WET STONE ECO** evenly using a flat paintbrush, wax applicator, or microfibre pad, making sure to also impregnate the grout.
To achieve the desired enhanced gloss effect on absorbent surfaces, apply a second coat once the first coat has dried (after 4 hours), following the above instructions.
For outdoor applications: we recommend applying the product once a year to maintain an optimal enhanced effect.
Wait at least 8 hours before walking on the surface.

CLEANING OF TOOLS: clean with water after use.
For ordinary maintenance: use a diluted solution of **CLEANER PRO** (1:200)

Caution:
Do not apply on materials with smooth, honed or polished finishes.
Since there are so many different materials, before applying the product we recommend testing it on a small area of the surface to verify the tone-enhancing effect. Do not apply the product outdoors if rain is forecast.
The product cannot be applied on substrates subject to rising damp and in humid environments with standing water (showers, saunas, Turkish baths, etc.).
*If the product is applied incorrectly or to thoroughly deep clean the surface, remove **WET STONE ECO** using **NOPAINT STAR**.*
Do not walk on the surface until it is completely dry.