LONGLIFE

GLOSSY PROTECTIVE WAX

TERRACOTTA, QUARRY TILES, SLATE, NATURAL STONE, AGGLOMERATES, RUBBER AND PVC, LAMINATE FLOORING, LINOLEUM, RESIN, VINYL SURFACES




WHAT IT'S FOR

- Protects floors subjected to high traffic.
- Perfect for flooring made from rubber, PVC, vinyl, plastic laminates, linoleum and resin.
- Ideal for protecting unpolished natural stone, granite and terracotta surfaces.
- Excellent also for maintaining quartz concrete floors treated with **BETON**.
- Generates a high-sheen and ultra-protective polymer surface film.
- Ideal for protecting polished natural stone floors in public areas.

ADVANTAGES

- No need to polish.
- High adhesion strength.
- Easy to apply.
- Can be undiluted or diluted as necessary.
- Maintenance can be carried out using a single-disc cleaning machine at high speed.



COVERAGE

COVERAGE (1 litre):	
Terracotta	30 m²
Stone	30-40 m²
Rubber/PVC, plastic laminates, Linoleum, Resin (undiluted)	30 m²
Rubber/PVC, plastic laminates, Linoleum, Resin (diluted 1:10)	300 m²

Coverage shown is indicative and refers to single coats

Packaging

1 litre: boxes of 12.
5 litres: boxes of 4.

WARNINGS
- Keep out of reach of children.
- Do not disperse into the environment after use.

TEMPERATURES
Storage temperature: from 5° to 30° C.
This product must be applied to surfaces with temperature between 10°C and 30°C.

HOW TO USE IT

Dilution:
either undiluted or diluted according to requirements.
For protecting surfaces:
apply one coat of the undiluted product evenly and continuously on a clean and dry floor, using a fleece pad or other applicator. Wait 1 hour. Then apply a second coat at right angles to the first. When dry, the floor will shine without requiring polishing.
When treating highly absorbent terracotta and natural stone surfaces, we recommend first applying a base coat of **FOB XTREME** or **W68**. Wait 24 hours before applying **LONGLIFE**.
Renewal of the sheen (every 2-3 months): after cleaning the surface with a diluted solution of **CLEANER PRO** (1:200), apply **LONGLIFE** by diluting 500 ml of product in 5 litres of water. The floor can be walked on once dry.
Restoration of the protection: remove the wax from the surface using the **PS87 PRO** detergent, diluted 1:5. Rinse the surface. Apply **LONGLIFE** undiluted on the dry and clean floor using fleece or other applicator. The floor can be walked on once dry.
CLEANING OF TOOLS: clean with water after use.
For ordinary maintenance: use a diluted solution of **CLEANER PRO** (1:200)

Caution:
Do not walk on floor while it's drying and do not repeat application on treated areas which are not yet dry.
*To remove this wax, use the specific wax-remover **PS87 PRO**.*
Do not use the product on external surfaces, in damp environments and where water puddles may form (bathrooms, showers).
Since there are so many different materials, before applying the product we recommend testing it on a small area of the surface to check for any colour changes.