SATIN

SATIN-EFFECT PROTECTIVE WAX

TERRACOTTA, QUARRY TILES, NATURAL STONE, UNPOLISHED AGGLOMERATES, CONCRETE, CONCRETE TILES



WHAT IT'S FOR

- Ideal both for treatment and maintenance.
- Protects unpolished natural stones (limestone, slate, etc.), red stoneware, non-vitrified quarry tiles and various types of terracotta.
- Recommended for treating floors made of: slate, manufactured stone and cement tiles.
- Highly recommended for maintenance of marble and natural stone with brushed finish.

ADVANTAGES

- A 3-in-one solution: protects, maintains and gives floors an excellent finish.
- Original new satin look.
- Ideal to create prestigious floors: enhances the beauty of the surface.
- Easy to apply and maximum coverage.
- Does not degenerate with maintenance.



COVERAGE

COVERAGE (1 litre):	
Terracotta	30 m²
Stone	30-40 m²

Coverage shown is indicative and refers to single coats

Packaging

1 litre: boxes of 12.
5 litres: boxes of 4.

HOW TO USE IT

Dilution:
either undiluted or diluted according to requirements.
For protecting surfaces:
using fleece or other applicator, apply an even coat of the product on the clean and dry floor. After 1 hour, apply a second coat at right-angles to the first. The floor can be walked on after roughly half an hour.
When treating highly absorbent materials, we recommend applying a coat of **FOB XTREME** or **W68** beforehand. Wait 24 hours before applying **SATIN**.
Renewal of the finish (every 2-3 months):
after having cleaned the surface with a diluted solution of **CLEANER PRO** (1:200), apply SATIN by diluting 500 ml of product in 5 litres of water. The floor can be walked on once dry.
Restoration of the protection:
remove the wax from the surface using the **PS87 PRO** detergent, diluted 1:5. Rinse the surface. Apply the undiluted wax on the dry floor using fleece or other applicator. No need to polish.
CLEANING OF TOOLS: clean with water after use.
For ordinary maintenance: use a diluted solution of **CLEANER PRO** (1:200**)**

WARNINGS
- Keep out of reach of children.
- Do not disperse into the environment after use.
- The product is sensitive to frost: store it as indicated on the label.

TEMPERATURES
Storage temperature: from 5° to 30° C.
This product must be applied to surfaces with temperature between 10°C and 30°C.

Caution:
Do not walk on floor while it's drying and do not repeat application on treated areas which are not yet dry.
*To remove this wax, use the specific wax-remover **PS87 PRO**.*
Do not use the product on external surfaces, in damp environments and where water puddles may form (bathrooms, showers).
The product can change the appearance of the material, first spot test a small surface area to check for any changes.