



TECHNICAL DATASHEET



- ✔ Fast-drying, ready-to-use gritty primer
- ✔ For use on flooring grade asphalt, bitumen, steel and existing vinyl tiles, ceramic and porcelain
- ✔ Designed to create a textured surface to enhance adhesion



Drying Time
15-60 mins



Coverage
35-50m² per 5L



SURFACE PREPARATION

Proper preparation of every substrate is essential for ensuring both the performance and durability of any installation. In accordance with BS 5385 and BS 8203, all substrates must be stable, level, clean, dry, and structurally sound, free from any materials that could hinder adhesion. This includes, but is not limited to, dust, debris, grease, oil, laitance, sealers, wax, and curing compounds, all of which should be removed by mechanical means. It is also important to verify that the substrate and background are sufficiently robust to support the weight of the compound, along with any final floor or wall finishes and associated fixing products.

APPLICATION

Before use, shake or stir thoroughly to ensure the aggregates are evenly distributed throughout the primer. Apply a thin, uniform coat across the entire surface using a paint roller, brush, or sponge. Avoid excessive application, as this can cause a surface film to form — full coverage is required, but only in a light layer. After application, allow the primer to dry until it is touch-dry before proceeding with tiling or levelling. Depending on ambient temperature drying will typically take 15-60 minutes: warmer conditions will shorten this time while cooler temperatures will extend it. Once primed, keep the area free from foot traffic.

Seal the container immediately after use to prevent evaporation or contamination. Clean all tools with warm water straight after application.

Note: Do NOT dilute primer with water.

TECHNICAL DATA	
Unit Size:	5L
Colour:	Green
pH @ 20°C:	~8
Viscosity	3,500 - 6,000cP

CLEANING

Tools should be thoroughly cleaned in water to remove excess materials immediately after use.

STORAGE

Store in a closed original container at temperatures between 5°C and 30°C and out of direct sunlight and frost.

SHELF LIFE

Shelf life is 12 months from manufacture in above conditions.

Coverage

Approx. 9-13m² per KG

HEALTH & SAFETY

Please ensure that appropriate PPE is used when preparing, mixing and applying products. Always wash hands before consuming food and make sure that materials are kept safely out of reach of children and animals. Please dispose of packaging and waste appropriately. A full Safety Data Sheet relating to this product is available from www.premtool.com.

QUALITY ASSURANCE

All products are manufactured in a plant whose quality management system is certified / registered as being in conformity with BS EN ISO 9001, ISO 14001 and ISO 45001. Premtool products are guaranteed against defective materials and manufacture and will be replaced or money refunded if the goods do not comply with our promotional literature. We cannot however accept responsibility arising from the application or use of our products because we have no direct or continuous control over where and how our products are used. All Premtool products are sold subject to our terms and conditions of sales, copies of which may be obtained upon request.