

**JUST DRILL
AND FILL!**

Fix-A-Floor®

BONDING ADHESIVE FOR LOOSE & HOLLOW TILE, MARBLE, STONE & WOOD

**TECHNICAL
DATA SHEET**

www.fixafloor.co.uk

sales@fixafloor.co.uk

Customer Service: 0121 270 8883

Fix-A-Floor Repair Adhesive is an extra strength customized formula created for the specific use of Re-Bonding Loose and Hollow Tile, Marble, Stone, & Wood floors without the expense and mess of removing or replacing.

PHYSICAL & CHEMICAL PROPERTIES:

Weight Per Gallon: 8.9 lb/gal

Specific Gravity: Approx. 1.07

Total Non-Volatile % Solids (Weight): 55%

Viscosity: 2000 cps

Consistency/Appearance: White color, water like

pH (initial): Approx. 5

Odor: Low

Flash Point: Non-Flammable, > 200° F

OSHA Flame Class: IIIB

Working Time/Open Time: 30 minutes @ 72° F

Coverage: 0.48 sq ft @ 1/4" layer

Freeze/Thaw Stability: Pass 5 Cycles (ASTM C731)

Shelf Life: Up to 3 years @ 72°F

Full Cure: 24 Hours

Storage Conditions: 40°F to 90°F (5°C to 32°C)

Application Temperature: 50°F to 90°F (10°C to 32°C)

Service Temperature: -20°F to 180°F (-29°C to 82°C)

Adhesion Strength (Tile to Wood): 48 lb/in²

Clean-Up: Water

FEATURES:

- Provides excellent adhesion to a wide variety of porous and non-porous substrates
- Compatible with an assortment of plasticizers, solvents, fillers and other modifiers
- Provides a strong yet permanently flexible adhesive bond.
- 100% Eco-Friendly, Non-Hazardous
- Works for interior & exterior applications

ADHERES TO:

- Ceramic Tiles
- Marble Tiles
- Wood Flooring & Subflooring
- Laminate Flooring
- Cement Subflooring

SPECS:

- ASTM C482 (Modified)
- Compliant with FDA Reg. 21 CFR 175.105, CFR 176.170, and 21 CFR 176.180

RECOMMENDATIONS/LIMITATIONS:

- After initial application, place weight on the application area and let it remain in place for 24 hours
- Stress on tiles due to improper installation will limit the success of the product. Properly installed movement joints should be used.
- This product is recommended for small/squeaky wood floor applications. If a larger wood floor area needs to be repaired, Fix-A-Floor® Polyurethane Wood Flooring Repair is recommended for use.
- If the tile has been completely removed, Fix-A-Floor® can be used as a general adhesive to reattach it.
- When using the product on underfloor heating elements, turn the heating elements off for 48 hours before, during, and after application.
- Fix-A-Floor® is not recommended for tile repair in areas subject to high moisture, such as showers and pools.
- Fix-A-Floor® is not recommended for use on carpet flooring.

LIMITED WARRANTY:

This product is warranted to be free of manufacturing defects. If a manufacturing defect is found within one year from the date of purchase, such defective product shall be replaced. No warranty either expressed or implied is made regarding the performance of this product since conditions under which these goods are transported, stored, used, or applied are beyond our control. This warranty is made in lieu of all other warranties either expressed or implied and the seller shall not be responsible for consequential, incidental, special or other damages no matter what the cause.

CRITERIA	STATUS
CARB Compliance	Yes
Prop 65 Ingredients	No
DOT Proper Shipping Name	Not Regulated by DOT
DOT Hazard	None
VOC Content	See MSDS

CAUTION: NOT FOR INTERNAL CONSUMPTION. KEEP OUT OF REACH OF CHILDREN & PETS. KEEP FROM FREEZING. (See SDS for additional safety information)