

DIRT REPELLENT

**TEXTURED PORCELAIN TILES, UNPOLISHED
PORCELAIN TILES, LAPPATO PORCELAIN TILES**



WHAT IT'S FOR

- Makes cleaning quick and easy and surfaces hygienic
- Improves the material's resistance to dirt
- Maintains the original appearance of the material over time

ADVANTAGES

- Provides prolonged protection over time
- For interior and exterior use
- High coverage
- Does not alter the material's anti-slip rating (tests conducted in conformity with B.C.R.A. and ASTM C 1028-2007 methods).
- Does not form surface film
- UV resistant and non-yellowing



PICTURES: by courtesy of Ceramiche Atlas Concorde S.p.a.

COVERAGE

With one litre:

**Textured, natural and Lappato
porcelain tiles up to 70 m²**

Coverage is indicative of one coat and may vary according to the material.

Packaging

500ml: boxes of 12.

WARNINGS

- This is a solvent-based product, the room should be aerated during application.
- Keep out of reach of children.
- Do not disperse into the environment after use.
- The use of a single-disc cleaning machine is permitted only if it is perfectly undamaged.

TEMPERATURES

Storage temperature: from 0°C to 30°C
The product should be applied to materials with temperature between 5° and 30°C.

HOW TO USE IT

No dilution required: The product is ready to use.

Application for new installations:

1. Wash the floor thoroughly using **DETERDEK PRO** (concrete grout joints) or **CR10** (epoxy grout).
2. Apply **STOP DIRT** to a clean and dry floor also treating the grout, covering evenly with a fleece or other suitable applicator. Advice from the expert: Given the product's high coverage, apply a moderate quantity of product to treat 2-3 m² of surface area at a time.
3. Rub the surface with a cloth or floor scrubber with white disc.
4. Fully remove all residues within 10 minutes, either manually using a microfibre cloth or with the single-disc floor scrubber.
5. After at least 12 hours, before treading on the treated surface, remove any product residues using a clean microfibre cloth.

Application on untreated surface to be restored:

1. Wash the floor using **PS87 PRO** and/or **DETERDEK PRO**.
2. Apply **STOP DIRT** on the dry surface in the manner described above.

Caution:

The product may enhance the colour of the material or grouting; carry out a spot test beforehand.

Aerate rooms during use.

Do not apply to matt-finish lappato porcelain tiles.